

Indoteak Design 100% FSC Reclaimed Teak Tile

ACCLIMATION:

When teak tile has arrived at location of installation, reclaimed teak tile should be allowed to acclimate on location for 4-5 days prior to installation.

SUBSTRATE:

This reclaimed teak tile should then be installed on a clean, sound, flat substrate. All substrate material must be dry, clean, and flat.

- The following substrates may be used with our teak tiles:
- Fully cured concrete substrate
- Cement backer board
- Gypsum board (dry area only)

GROUT:

Epoxy grout is the only choice for our reclaimed teak tiles. Due to the moisture in the adhesive during installation, our teak tiles may warp if traditional water mix adhesives are used. Please only use Epoxy based grout (floors) or epoxy adhesive(walls)

Prior to Grouting:

Prior to grouting joints, after the setting adhesives is completely dry the following day. It is not recommended to set our teak tile and grout in same day. If set and grouted in same day, our teak tiles will not have a chance to acclimate during the drying process of the setting material and this may crack the grouted joints.

Grouting:

Test grout on sample piece of tile to ensure that color and appearance is as desired.

During application, when sponging the grout off the tile surface, a soft bristle brush is helpful to remove grout from the seams in the wood surface. If the grout is allowed to fully dry in the surface seams, it can be very difficult to remove. Our teak tile does not have to be sealed after grouting, as urethane grout does not require sealing.

MAINTENANCE:

Our 100% reclaimed teak tile may be regularly cleaned using, a gentle water based cleaner.

Indoteak provides product information and information concerning certain installation procedures and maintenance practices to assist each of its customers in making selection, usage, installation and maintenance decisions, to maximize their enjoyment of its products. Customer's selection and usage of Indoteak's products and the installation procedures and maintenance practice employed by each customer are outside the direction and control of Indoteak's and are strictly and completely the choice and responsibility of each customer. Indoteak does not warranty any product for any specific use nor any installation procedure or maintenance practice and expressly disclaims all claims asserted after customer installation or usage or Indoteak's product begin.

